

KTD-10 Rod Series

量程: 0-125mm 可选模拟输出:

0~5V,0~10V,4-20mA 标准信号;

标准 100mm 屏蔽线引出。

适应狭小的安装位置, 如医疗设备、自动化控制、变频调速等。

Stroke range: 0-125mm,

Analog output:0-5V,0-10V,4-20mA with 100mm shield wire;

Suitable for narrow space situation, such as medical equipment, automation control, frequency control etc.

<b>KTD-10 拉杆系列</b>	单位/量程	10	15	25	50	75	100	125
电性行程	mm	11	16	26	51	76	101	126
可用电性行程	mm	10	15	25	50	75	100	125
电阻±20%	kΩ	1.0			5.0			
独立线性率	±%	0.05						
机械行程 (M.T)	mm	11	16	26	51	75	101	126
输出范围		分压器						
解像度		无限						
使用温度范围	C°	-50 + 120						
尺寸 A	mm	37.5	42.5	52.5	77.5	102.5	127.5	152.5

尺寸仅供参考, 如有更改, 恕不另行通知.

<b>KTD-10 Rod Series</b>	Units	10	15	25	50	75	100	125
Total Electrical Travel (T.E)	mm	11	16	26	51	76	101	126
Active Electrical Travel (A.E)	mm	10	15	25	50	75	100	125
Resistance Range ±20%	kΩ	1.0			5.0			
Independent Linearity	±%	0.05						
Mechanical Travel (M.T)	mm	11	16	26	51	75	101	126
Output		Voltage divider						
Resolution		Infinite						
Operating Temperature	C°	-50 + 120						
Dimensions A	mm	37.5	42.5	52.5	77.5	102.5	127.5	152.5

Dimensions for reference only, subject to change with.