

KTD-22 Hinged Joint Type

量程: 0-125mm 可选模拟输出:
0~5V,0~10V,4-20mA 标准信号;
标准 100mm 屏蔽线引出。
适应狭小的安装位置, 如医疗设
备、自动化控制、变频调速等。

Stroke range: 0-125mm,
Analog output:0-5V,0-10V,4-20mA
with 100mm shield wire;
Suitable for narrow space situation,
such as medical equipment,
automation control, frequency control etc.

KTD-22 铰链式	mm	10	15	25	50	75	100	125	150	175	200	225	250	275	300	400
电性行程	mm	12	17	27	52	77	102	127	152	177	202	227	252	277	302	402
可用电性行程	mm	10	15	25	50	75	100	125	150	175	200	225	250	275	300	400
电阻±20%	kΩ	1.0							5.0							
独立线性率	±%	0.05														
机械行程 (M.T)	mm	15	20	30	55	80	105	130	155	180	205	230	255	280	305	405
输出范围		分压器														
解像度		无限														
使用温度范围	C°	-50 + 120														
尺寸 A	mm	75	80	90	115	140	165	190	215	240	265	290	315	340	365	465
总长		130	135	145	170	195	220	245	270	295	320	345	370	395	420	520

尺寸仅供参考, 如有更改, 恕不另行通知。

KTD-22 Hinged Joint Type	mm	10	15	25	50	75	100	125	150	175	200	225	250	275	300	400
Total Electrical Travel (T.E)	mm	12	17	27	52	77	102	127	152	177	202	227	252	277	302	402
Active Electrical Travel (A.E)	mm	10	15	25	50	75	100	125	150	175	200	225	250	275	300	400
Resistance Range ±20%	kΩ	1.0							5.0							
Independent Linearity	±%	0.05														
Mechanical Travel(M.T)	mm	15	20	30	55	80	105	130	155	180	205	230	255	280	305	405
Output		Voltage divider														
Resolution		Infinite														
Operating Temperature	C°	-50 + 120														
Dimensions A	mm	75	80	90	115	140	165	190	215	240	265	290	315	340	365	465
Total Dimensions		130	135	145	170	195	220	245	270	295	320	345	370	395	420	520

Dimensions for reference only and subject to change without prior notice.